

uFix

Indoor LED Panel Display

1.9p | 2.6p | 3.9p | 4.8p

RELOOK

Integrated Display Solutions



16 RUE MILLEWEE L-7257 HELMSANGE WALFERDANGE, LUXEMBOURG



TEL +352 26 43 22 03



FAX +352 26 43 22 04



CONTACT@RELOOK.LU

WWW.RELOOK.LU

RELOOK

Integrated Display Solutions

PIXEL PITCH	1.9 mm	2.6 mm
LED TYPE	3-in-1 Black SMD	3-in-1 Black SMD
LED CONFIGURATION	1Red, 1Green, 1Blue	1Red, 1Green, 1Blue
BRIGHTNESS	600 cd/m ²	900 cd/m ²
CABINET SIZE	500 mm * 500 mm * 83 mm	500 mm * 1000 mm * 83 mm
PIXELS PER PANEL	256×256 Dots	192×384 Dots
WEIGHT	7.8 kg/panel	13 kg/panel
MATERIAL	Die-cast Magnesium	Die-cast Magnesium
ENVIRONMENT	Indoor	Indoor
INGRESS PROTECTION	IP30	IP30
MAINTENANCE	Front and Rear	Front and Rear
GAP BETWEEN MODULES	Seamless	Seamless
CONTRAST RATIO	3000 : 1	3000 : 1
MAXIMUM INPUT POWER	120W / panel	240W / panel
TYPICAL INPUT POWER	40W / panel	80W / panel
STANDARD MOUNTING CONFIGURATION	Hanged, Floor-mounted	Hanged, Floor-mounted

PIXEL PITCH	3.9 mm	4.8 mm
LED TYPE	3-in-1 Black SMD	3-in-1 Black SMD
LED CONFIGURATION	1Red, 1Green, 1Blue	1Red, 1Green, 1Blue
BRIGHTNESS	900 cd/m ²	900 cd/m ²
CABINET SIZE	500 mm * 1000 mm * 83 mm	500 mm * 1000 mm * 83 mm
PIXELS PER PANEL	128×256 Dots	104×208 Dots
WEIGHT	13 kg/panel	13 kg/panel
MATERIAL	Die-cast Magnesium	Die-cast Magnesium
ENVIRONMENT	Indoor	Indoor
INGRESS PROTECTION	IP30	IP30
MAINTENANCE	Front and Rear	Front and Rear
GAP BETWEEN MODULES	Seamless	Seamless
CONTRAST RATIO	3000 : 1	3000 : 1
MAXIMUM INPUT POWER	240W / panel	240W / panel
TYPICAL INPUT POWER	80W / panel	80W / panel
STANDARD MOUNTING CONFIGURATION	Hanged, Floor-mounted	Hanged, Floor-mounted